# Affiliates vs Hunters: Fighting the DarkSide

**G** socprime.com/blog/affiliates-vs-hunters-fighting-the-darkside/

#### Emanuele De Lucia



### Introduction

On **August 2020** a new type of malware, belonging to the *Ransomware* category, appeared in the cyber threat landscape. Threat actor responsible for its development called it "**DarkSide**" and, like others piece of malware of this type, is operated in **Big Game Hunting** (BGH) campaigns. Around more or less the same time, a DLS (**Dedicated Leak Site**) was made available on the *darkweb* (behind the **TOR** network) in order to report the first victims.

**On their DLS DarkSide** operators claimed to be experienced in conducting cyber operations, having previously used other, not better identified, ransomware variants. Indeed, some characteristics of their first operations support the hypothesis that the group could be a former affiliate of some other **R-a-a-S** (Ransomware as a Service) program that chosen to write their own ransomware likely to avoid sharing the profits of criminal activities with third parties.

### Insights

**DarkSide** is a *well-written* malware family not much changed over the time if compared to the first versions analyzed on August / September 2020. Usually, the samples belonging to this family present some features aimed at making the analysis more harder. For example, in a recent sample (sha256:

17139a10fd226d01738fe9323918614aa913b2a50e1a516e95cced93fa151c61), at **0040182A** we find a *sub* aimed at dynamically resolving **DLLs** and **API** through *LoadLibrary* / *GetProcAddress*. *sub\_4016D5*, *sub\_4013DA* and *sub\_401AC3* are also involved in this process. The following screenshot shows a chunk of code extracted from the whole function designed for this purpose:

```
push
        esi
        LoadLibraryA
call
        ebx, eax
mov
push
        dword ptr [esi-4]
push
        esi
call
        sub_4013DA
                         ; API
        eax, [esi-4]
mov
lea
        esi, [esi+eax]
        ecx, 23h
mov
call
        sub_401AC3
lodsd
push
        eax
push
        esi
call
        sub 4016D5
push
        esi
                         ; Kernel32
call
        LoadLibraryA
        ebx, eax
mov
push
        dword ptr [esi-4]
        esi
push
call
        sub_4013DA
                         ; API
```

This can be a useful place to create a *code* based **Yara** rule aimed at potentially hunting further variants of the same malware family. After having selected several representative chunks we can obtain something similar to the following:

```
rule DarkSide_Ransomware_827333_39928 : CRIMEWARE {

meta:

author = "Emanuele De Lucia"

description = "Detects possible variants of DarkSide ransomware"

hash1 = "17139a10fd226d01738fe9323918614aa913b2a50e1a516e95cced93fa151c61"

/*

call 0x4016d5

push esi

call 0x408195

mov ebx, eax

push dword ptr [esi – 4]push esi

call 0x4013da
```

```
mov eax, dword ptr [esi – 4]lea esi, [esi + eax]mov ecx, 0x23
*/
strings:
$ = { E8 [4] 56 E8 [4] 8B D8 FF 76 ?? 56 E8 [4] 8B 46 ?? 8D 34 06 B9 ?? ?? ?? ?? }
condition:
any of them
}
```

**Darkside** employs also techniques for privilege escalation and **UAC** (User Access Control) bypass. The technique observed in this case is known as **CMSTPLUA UAC Bypass** and exploits the **ShellExec** function by **CMSTPLUA COM** interface **{3E5FC7F9-9A51-4367-9063-A120244FBEC7}**. This allow to start a process with elevated permissions, according to the following graph:



Powershell is used in order to delete shadow copies preventing the recovery of previously backed up files through them according to the following syntax:

```
powershell -ep bypass -c
```

```
"(0..61)|%{$s+=[char][byte]
('0x'+'4765742D576D694F626A6563742057696E33325F536861646F77
636F7079207C20466F72456163682D4F626A656374207B245F2E44656C65746528293B7D20'
.Substring(2*$_,2))};iex $s"
Decoded:
Get-WmiObject Win32 Shadowcopy | ForEach-Object {$ .Delete();}
```

A quick **Sigma** rule can be employed in order to hunt for similar *systems-side* behaviors.

title: Detects possible DarkSide infection through PowerShell cmdline used to delete Shadow copies status: stable description: Detects possible DarkSide infection through PowerShell cmdline used to delete Shadow copies author: Emanuele De Lucia references: – internal research

```
tags:

- attack.t1086

- attack.t1064

date: 2020/12/01

logsource:

category: process_creation

product: windows

detection:

selection:

Image|endswith:

- '\powershell.exe'

CommandLine|contains|all:

- '(0..61)|%%{$s+=[char][byte]'

- '4765742D576D694F626A6563742057696E33325F536861646F77636F7079207C
```

```
20466F72456163682D4F626A656374207B245F2E44656C65746528293B7D20'
condition: selection
level: high
```

Before executing the main payload, the sample performs several other activities like information gathering (f.e. get Disks Info)



and a comparison of system services with a predefined list to stop those ones that could affect the files encryption process

```
do
{
    v3 = 0;
    v4 = (_WORD *)dword_CF0914;
    while ( 1 )
    {
        if ( !v3 )
        {
            dword_CF0CF6(*v2);
            v3 = 1;
        }
        if ( wcsstr(*v2, v4) )
        {
            v9 = OpenService(v10, *v2, 65568);
            if ( v9 )
                break;
        }
        result = dword_CF0CF2(v4);
        v4 += result + 1;
        if ( !*v4 )
            goto LABEL_11;
    }
    sub_CE13DA(&v5, 0x1Cu);
    ControlService(v9, 1, &v5);
    DeleteService(v9);
    result = CloseServiceHandle(v9);
```

The following are the services malware looks for in the analyzed sample:

sql oracle ocssd dbsnmp synctime agntsvc isqlplussvc xfssvccon mydesktopservice ocautoupds encsvc firefox tbirdconfig mydesktopqos ocomm dbeng50 sqbcoreservice excel infopath msaccess mspub onenote

```
outlook
powerpnt
steam
thebat
thunderbird
visio
winword
wordpad
notepad
```

These areas can likewise be considered in order to extract bad-known pieces of code:

```
rule DarkSide Ransomware 827333 39929 : CRIMEWARE {
meta:
author = "Emanuele De Lucia"
description = "Detects possible variants of DarkSide ransomware"
hash = "17139a10fd226d01738fe9323918614aa913b2a50e1a516e95cced93fa151c61"
/*
push 0x10020
push dword ptr [edi]push dword ptr [ebp – 4]call dword ptr [0xcf0e66]mov dword ptr [ebp – 8],
eax
cmp dword ptr [ebp - 8], 0
je 0xce4d83
push 0x1c
lea eax, [ebp – 0x30]push eax
call 0xce13da
lea eax, [ebp – 0x30]push eax
push 1
push dword ptr [ebp – 8]call dword ptr [0xcf0e6a]push dword ptr [ebp – 8]call dword ptr
[0xcf0e6e]*/
strinas:
$ = {68 [4] FF 37 FF 75 ?? FF 15 [4] 89 45 ?? 83 7D [2] 74 ?? 6A ?? 8D 45 ?? 50 E8 [4] 8D
45 ?? 50 6A ?? FF 75 ?? FF 15 [4] FF 75 ?? FF 15 ?? ?? ?? ?? ??
condition:
any of them
}
```

After the encryption phase, **Darkside** is designed to communicate to its command and control server in order to share details relating to the victim (victimID) as well as further parameters useful for recovering encrypted files and identifying the affiliate.

Most probably these network capabilities have been added in order to support the R-a-a-S model. In the analyzed sample, the CnC (Command and Control) is attested over the domain name **securebestapp20.com**. Detecting network activities potentially related to this threat

could therefore involve writing SNORT rules similar to the following:

alert udp \$HOME\_NET any -> any 53 (msg:"DNS request for blacklisted domain 'securebestapp20.com'"; content:"\0f\securebestapp20\03\com\00\";nocase; reference:url,https://www.emanueledelucia.net/; sid:[SID HERE]; rev:1;)

This domain name has been created on **16/09/2020** and, according to my visibility, at the time of writing it has a history of **two** (2) A record associated. The interesting one is linked to the IP **185.105.109.19**. Could be interested to note that the **pDNS** count value for this domain name from **21/09/2020** (day of first observed resolution to **185.105.109.19**) to **05/01/2021** (day of last observed resolution to **185.105.109.19**) is less than **180** and that most of them occurred from early November until today. This suggests a growth of the spread and obviously of the **R-a-a-S** business as well. In general, moreover, this number is also consistent with the low overall volume of **DarkSide** campaigns observed at least until mid-November 2020. This is further confirmed by the *payload-side* global visibility I can dispose of for this malware family.

Following are shown detection hits for DarkSide malfamily until the end of the year where it's possible to observe a general increase in the detection rates towards December 2020.



### Welcome to Darkside

On **11/10/2020** a user posted an announcement titled "*[Affiliate Program] Darkside Ransomware*" on a **Russian-speaking** darkweb forum. The text contained in that post officially started the project's affiliate program. Press articles has been used in order to advertise the program itself as well as the skills of the group that are "*aimed only at large corporations*" as originally posted by threat actor itself:

### Кто мы?

-----

Мы продукт нацеленный только на крупные корпорации. Можно детальнее прочесть тут:



Beware This Sinister New 'Dark Side' \$1 Million Cyber Threat, You Must Beware this brand new threat that targets those who "can afford to pay," and has already made more than \$1 million in less than two weeks.

F www.forbes.com



Mysterious 'Robin Hood' hackers donating stolen money

Experts and charities are puzzled by hackers who've started donating stolen money. bbc.com

In the affiliate program are not welcome, among others, English speaking personalities, employees of the secret service, security researchers, the greedy (at least so I seem to understand) etc.etc.

#### Кого мы НЕ ищем?

-----

- Англоговорящих личностей.
- Сомнительных личностей, сотрудников секретной службы и аналитиков ИБ компаний.
- Тех, кто ставит дедики и занимается деятельностью отличимой от поставки сетей.
- Любые темы и предложения отличимые от этого поста.
- Желающих обучиться пентестингу и зарабатывать миллионы.
- Любителей ставить 100кк выкупа за 3.5 сервера.

There are, moreover, some rules to be respected, like avoiding to target entities within countries belonging to the **CIS** (**Содружество Независимых Государств**), including Georgia and Ukraine, or those operating in education, medicine, public and non-profit sector.

As you might imagine for any other job, there is a selection to go through in order to be included in the program. This includes an *interview* to check the candidate's skills and experiences, such having been affiliated with some other program previously. The group offers a **Windows** and **Linux** version of DarkSide ransomware plus an admin panel, a leak site, and a **CDN system** for data storage.

#### О софте?

Мы готовы предоставить партнерам

- Windows[full ASM, salsa20 + rsa 1024, i / o, own implementation of salsa and rsa, fast / auto (improved space) / full, token impersonalization for working with balls, slave table, freeing busy files, changing file permissions, arp scanner, termination of processes, services, drag-and-drop and much more].
- Linux [C++, chacha20 + rsa 4096, многопоточен (в том числе Hyper-threading, аналог i/о на windows), поддержка урезанных сборок ос (esci 5.0+), fast / space, настройка каталогов и много другого].
- Админ панель [full ajax, автоматический прием Bitcoin, Monero, генерация win / lin билдов с указанием всех параметров (процессы, сервисы, папки, расширения...),
- отстук ботов и детальная статистика по результативности компании, автоматическое распределение и вывод средств, саб-аккаунты, онлайн чат и множество другого]. • Leak site [скрытые посты, поэтапная публикация данных таргета и еще множество функционала].
- СОN система для хранения данных [Получение квот, быстрая загрузка данных, хранение 6м с момента загрузки].

## So, do you have ESXi?

At the end of November 2020, a **Linux** variant of **DarkSide** ransomware was uploaded to a *well-known* online malware repository. It had a detection rate, at the time of upload, practically non-existent. Even at time of writing (**Jan 2021**) the detection rate is very low (**2/63**). It seems to have a quite different purpose respect to the Windows counterpart. While the latter is born to encrypt all user files on a workstation (documents, images, PDFs and so on...), the Linux version has been created to damage virtual machines on servers. Indeed, the samples looks for extensions related to **VMWare** files like *.vmdk*, *.vmem*, *.vswp* and generic logs formats.

```
v19 = sub_436890(0LL);
v135 = sub_435130(v19, &v140);
std::string::string(&v139, "vmdk,vmem,vswp", &v164);
v20 = sub_436890(0LL);
v131 = sub_435130(v20, &v139);
v21 = sub_436890(0LL);
```

The ransom note is similar to the Windows one



and the output of the executable, once launched, confirms the focus on ESXi environments

Root Path/vmfs/volumes/
Key Size548 Bytes
Public KeyVALID
Part Size
Space SizeOmb
Min Size1mb
Search Extensionvmdk,vmem,vswp,log

as /vmfs/volumes/ is the default location of ESXi virtual machines. A strict Yara rule similar to the following can help in identifying Linux variants of DarkSide:

```
rule DarkSide_Ransomware_827333_39930 : CRIMEWARE {
  meta:
  author = "Emanuele De Lucia"
  description = "Detects possible variants of Linux DarkSide ransomware variants"
  hash1 = "da3bb9669fb983ad8d2ffc01aab9d56198bd9cedf2cc4387f19f4604a070a9b5"
  strings:
  $ = "vmdk,vmem,vswp,log" fullword ascii
  $ = "Vmdk,vmem,vswp,log" fullword ascii
  $ = "XChaCha20" fullword ascii
  $ = "Partial File Encryption Tool" fullword ascii
  $ = "main.log" fullword ascii
  condition:
  (uint16(0) == 0x457f and all of them)
  }
```

Also for the Linux version, communications to the outside world take place through the same domain name previously reported and a specially crafted URL for each victim. Through Sigma it's possible to write rules aimed at detecting DNS resolution requests to domain name where actually the command and control is attested:

```
title: Detects resolution requests to DarkSide Command and Control domain name
status: stable
description: Detects resolution requests to DarkSide Command and Control domain name
references:
- https://www.emanueledelucia.net/fighting-the-darkside-ransomware/
author: Emanuele De Lucia
date: 2020/12/01
tags:
- attack.t1071.001
logsource:
category: dns
detection:
selection:
guery:
```

- 'securebestapp20.com' condition: selection falsepositives:
- internal research level: high

### **Adversary Profile**

From mid-November 2020, following the affiliation program, it's currently more difficult to associate the exclusive use of **DarkSide** ransomware to a specific threat actor.

However, some similarities with **Revil** suggest that its developer may be familiar with this solution until speculating that it may be from a former Revil affiliate who, to have more control over the operations and not to divide the profits, launched his own project, further enhanced by an independent affiliate program. Regardless the specific actor behind the operations, **DarkSide** can be delivered via several vectors usually after gathering information about the target.

According to my visibility, at least one threat actor who used **DarkSide** adopted the phishing technique (<u>T1566</u>) in order to deliver a *first-stage* payload whose exploitation finally allowed the distribution of DarkSide variants within the victim environment. Other intrusion techniques involve exploiting vulnerabilities in exposed applications (<u>T1190</u>) in order to get a first foothold from which to perform lateral movements.

sha256	payload- delivery	da3bb9669fb983ad8d2ffc01aab9d56198bd9cedf2cc4387f19f4
sha256	payload- delivery	17139a10fd226d01738fe9323918614aa913b2a50e1a516e95c
domain	network- activity	securebestapp20.com

### Indicators of Compromise

**Observable Description Value** 

**Join SOC Prime's Detection as Code platform** to improve visibility into threats most relevant to your business. To help you get started and drive immediate value, book a meeting now with SOC Prime experts.

Join for Free Book a Meeting